

Product datasheet

L110260-06

LED filament bulb

G95 | 6W | E27 | clear




COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Type of light source

Lighting technology used	LED
Non-directional or directional	NDLS
Light source cap-type (or other electric interface)	E27
Mains or non-mains	MLS
Connected light source (CLS)	no
Color-tuneable light source	no
Envelope	no
High luminance light source	no
Anti-glare shield	no
Dimmable	yes

General product parameters

Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer	6		
Energy efficiency class	E		
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	700lm		
Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3000k		
On-mode power (P_{on}), expressed in W	6W		
Standby power (P_{sb}), expressed in W and rounded to the second decimal	-		
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-		
Colour rendering index, rounded to the nearest integer, or the range of CRI values that can be set	-		
Outer dimensions with out separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height: 135mm	Width: 95mm	Depth: 95mm
Spectral power distribution in the range 250 nm to 800 nm, at full-load			
Claim of equivalent power	yes, 70W		
Chromaticity coordinates (x and y)	x=0.459, y=0.416		

Parameters for directional light sources

Peak luminous intensity (cd)	-
Beam angle (degrees)	-
Beam angle range (Minimum) (degrees)	-
Beam angle range (Maximum) (degrees)	-

Parameters for LED and OLED light sources

R9 Colour rendering index	10
Survival factor	>0.9
Lumen maintenance factor	>0.96

Parameters For LED and OLED mains light sources

Displacement factor	>0.9
Colour consistency in McAdam ellipses	2
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	-
Flicker metric (W)	0.03W
Stroboscopic effect metric (W)	0.0016W

References / Links

For further products and actual information concerning lamps see
<https://www.besselinklicht.nl>

For Guarantee see
<https://www.besselinklicht.nl/retourneren-garantie>

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

home sweet home is a concept of Besselink licht import b.v.

home sweet home and this packaging design is a registered trademark of Besselink licht import b.v.

T +31 (0) 26 319 06 30 ■ E info@homesweethome.nl ■ I www.homesweethome.nl

Besselink licht import b.v.

Nieuwgraaf 10 ■ 6921 RJ Duiven ■ Nederland

E info@besselinklicht.nl ■ I www.besselinklicht.nl